

2/PRTS

09/09/2001 13:44:44
JC17 Rec'd PCT/PTO 06 AUG 2001
09/890253

1

DATA PROCESSING SYSTEM USING A DUAL MONITOR AND
CONTROLLING METHOD OF NETWORK SYSTEM THEREBY

Technical Field

5 The present invention relates to a data processing
system using a dual monitor and controlling method of
network system thereby, and more particularly, to a data
processing system using a dual monitor and controlling
method of network system thereby, which can process data
10 by a computer using a dual monitor, on which separate
contents are displayed respectively, as a display device.

Background Art

15 In general, a data processing result of a computer
is displayed on a monitor to show it to a user. The
contents displayed on the monitor is converted and
displayed into video signal through a video graphics
adapter (hereinafter, called as "VGA") controlled by a
processor.

20 The user of the computer, occasionally, works while
simultaneously loading several programs in one computer,
for example, works with the computer in a state that a
word processing program for word processing and a
browser program for communication are loaded at the same
25 time.

For example, when the user loads the word
processing program, several web-browsers, a graphic

editor program and others using the computer operated by an operating system of a window control type, links concerning the loaded programs are registered on a tray of a windows screen and a presently used program is
5 displayed on the monitor.

However, generally, one computer is connected to one monitor. Thus, even though several programs are loaded, only one screen corresponding to the presently used program is displayed on the monitor. Therefore,
10 when the user works confirming the processed result in respect with two or more programs at the same time, the user must select whenever the corresponding program on the window tray is needed, to pop up the needed program on the monitor.

15 To solve the problem, a windows 98 version having a multi-display function, which is an operating system developed by Microsoft Corporation, has been disclosed and widely used. The multi-display function means that two or more VGAs are connected to two monitors
20 respectively and each monitor displays the processed result by the program set by the user.

The multi-display function can be very conveniently used in case that the user must work confirming the processed contents in respect with two or more programs
25 at the same time after several programs are loaded. However, because two or more monitors are needed to use the multi-display function, a desk having a wide area is

required.

Meanwhile, if the computer is connected to an Internet to connect to a specific Homepage through a web browser, information provided by the corresponding
5 Homepage is displayed on the monitor.

However, most of the Homepages generally allows space for advertisement on a part of their own web page. Thus, the user must shut a window for the advertisement, which the user does not want, and enlarge or scroll the
10 window, which displays the required information.

However, an advertiser wants to show the ad contents without regard to the user's intention because ad effects are decreased if the user shuts the window for the advertisement without seeing the ad contents.
15 Conventionally, there are no systems and methods to satisfy both the user and the advertiser.

Disclosure of the Invention

It is, therefore, an object of the present
20 invention to provide a data processing system using a dual monitor and controlling method of network system thereby, which has an auxiliary monitor for displaying secondary information such as an advertisement besides a main monitor for displaying processed contents of
25 programs often used by a user, and which displays the processed contents of the programs on the main monitor and displays the secondary information on the auxiliary

monitor, thereby improving efficiency in use of a computer.

It is another object of the present invention to provide a data processing system using a dual monitor
5 and controlling method of network system thereby, which constructs a network using computers using dual monitors to make an exchange of data with the other party convenient.

To achieve the above objects, the present invention
10 provides a data processing system using dual monitors including: a memory providing a data processing area using a program; at least one or more input means for inputting data; a first video graphics adapter (VGA) generating and outputting screen data for displaying a
15 result processed by at least one or more programs; a second graphics adapter generating and outputting screen data for displaying a result processed by at least one or more programs, the result being different from the contents displayed by the first VGA; a processor
20 processing data input through the input means using the memory and outputting the processed result through the first and second VGAs; a first monitor for displaying screen data output from the first graphics adapter; and
25 a second monitor for displaying screen data output from the second graphics adapter, wherein the processor displays the processed result of a main program presently used by a user through the first VGA and the

first monitor, processes information, which is different from the contents displayed on the first monitor and input from the outside, and displays the information through the second VGA and the second monitor, and in case of selecting one of user interfaces displayed through the first or second monitors, displays the processed result on the other monitor.

The data processing system further includes a sound processing part having a microphone for inputting sound signal and a speaker for outputting sound, which are integrated to the first and second monitors. The second monitor is constructed integrally with the first monitor and has a screen size smaller than that of the first monitor. The data processing system further includes a digital camera integrated with the dual monitors and for inputting video information, wherein video data input by the digital camera is input to the processor through the a universal serial bus (USB) port.

The processor further includes a communication interface for communicating with an external network to construct a network, and further includes a broadcasting receiving part for receiving TV/Radio broadcasting wave and outputting video and audio signals.

The video data received by the broadcasting
25 receiving part is output through one of the first and
second VGAs, and the first and second VGAs and the first
and second monitors are connected with one video cable

respectively, or connected with one video cable respectively, which integrates a plurality of lines for transmitting two video signals into one package.

In the present invention, a dual monitor for use in a computer system having a VGA outputting two video signals includes a first monitor for receiving and displaying a first information data comprising main processing contents of a program, which is presently being used by a user, output from a processor of the computer system; and a second monitor formed integrally with the first monitor, for receiving and displaying anyone of the first information data being displayed on the first monitor, a second information data and an ad data which are provided with the computer system through a network.

connected to the network as a video communication system, a digital camera is mounted on each computer, the user's picture is transmitted to the other party's computer, and at the same time, the user's picture is displayed on one of the first and second monitors, and the other party's picture is displayed on the other monitor.

As described above, according to the present invention, monitors for displaying different information are connected to a computer, thereby improving efficiency in use of the computer.

Brief Description of the Drawings

Further objects and advantages of the invention can be more fully understood from the following detailed description taken in conjunction with the accompanying drawings in which:

FIG. 1 is a block diagram of a structure of a data processing system using dual monitors according to the present invention; and

FIG. 2 is a block diagram of a network constructed by using the data processing system using dual monitors according to the present invention.

Best Mode for Carrying Out the Invention

The present invention will now be described in detail in connection with preferred embodiments with reference to the accompanying drawings. For reference,

like reference characters designate corresponding parts throughout several views.

FIG. 1 is a block diagram of a structure of a data processing system using dual monitors according to the present invention, and FIG. 2 is a block diagram of a network constructed by using the data processing system using dual monitors according to the present invention.

As shown in FIG. 1, the data processing system using a dual monitor according to the present invention includes: an input device having a keyboard 44a for inputting characters and symbols, a mouse 44b for changing a position of a pointer on a window or others; a processor 32 for analyzing, calculating and managing the input information; a memory device having a ROM 34 and a RAM 36 for memorizing required programs and data to help a processing work of a processor 30; a hard disk drive (HDD) 38, which is a storing device for storing data processed by the processor 32; a controlling device such as a bus controller, a drive (HDD, CD-ROM drive or others) controller and an external input/output (I/O) controller; an output device having a dual monitor 10, a speaker 22 or others for outputting the result processed by the processor; and a communication device for serving to transmit information between computers.

There are a LAN (Local Area Network) card, a modem and etc. as the communication device, and in the present invention, the communication device is connected to a

network 7 through the LAN card 38.

The dual monitor 10 includes: a first monitor 12 serving as a main monitor for displaying the processed result of program, which a user uses presently; and a
5 second monitor 14 mounted on the first monitor 12 and serving as an auxiliary monitor for displaying contents relating to or being different from the contents displayed on the first monitor 12.

The first and second monitors 12 and 14 are
10 constructed integrally with each other by a common housing. The first and second monitors 12 and 14 may be constructed with a CRT (Cathode Ray Tube) display, a LCD (Liquid Crystal Display) panel, or other display elements. In consideration of the bulk, it is preferable
15 to use the LCD panels for both of the monitors 12 and 14.

A digital camera 20 is mounted at the side of the second monitor 14 to input video information when it is used for a video telephone, and inputs video data to the processor 30 through a USB (Universal Serial Bus) port
20 44.

The video data processed and output from the processor 30 are input to the first and second monitors 12 and 14 through first and second video graphics adapters (VGAs) 46 and 48. In this embodiment of the
25 present invention, a system constructed by two VGAs is disclosed, but it may be constructed with a dual port VGA having two output ports according to circumstances.

the video cables connecting the video output port and the video input port are connected with each other by one video cable integrating the plurality of lines into one package for transmitting two video signals.

5 The present invention includes a broadcasting receiving part, i.e., a TV/R receiving part 50 for receiving TV/Radio broadcasting wave, such that one of the first and second monitors 12 and 14 may be used as a TV screen.

10 The TV/R receiving part 50 outputs TV video signal received by a control of the processor 30 through one of the first and second VGAs 46 and 48, and audio signal is output through a sound processing part 52, which will be described later, by the processor 30.

Therefore, the user can watch TV broadcasting through the second monitor 14 during using an Internet using a specific program through the first monitor 12, for example, a web browser. Especially, in case of receiving the radio broadcasting, because only audio signal is output, different programs may be processed through the first and second monitors 12 and 14.

It is possible that the dual monitor 10 has a broadcasting receiving part, which can receive TV/Radio broadcasting like the TV/R receiving part 50, the received broadcasting signals are transmitted to the processor 30 through a USB port 46, video signal of the broadcasting signals is output through one of the first

the users can input data while confirming a data input condition of the other party, thereby increasing the efficiency of work.

Furthermore, when a user interface provided by the program displayed on the first monitor 12, for example, a graphic user interface, is clicked with a mouse, the data processing system using the dual monitor according to the present invention displays a program connected to the corresponding user interface on the second monitor 14 (or to the contrary), such that a screen display area is enlarged by two monitors, thereby increasing the convenience in use of the computer.

Moreover, by using the digital camera 20 connected to the processor 30 of each of the computers 2a, 2b and 2c connected to the network 7 through the USB port 46, the data processing system according to the present invention may be used as the video communication system.

In other words, the user's picture captured with the digital camera mounted on the computer is transmitted to the other party's computer, and at the same time, the user's picture is displayed on one of his own first and second monitors, and the user's picture transmitted to the other party is displayed on the other monitor, and thereby the data processing system can be used as the video communication system.

Industrial Applicability

As previously described, the dual monitor connected to the computer for displaying different information increases the use of the computer.

5 While the present invention has been described with reference to the particular illustrative embodiments, it is not to be restricted by the embodiments but only by the appended claims. It is to be appreciated that those skilled in the art can change or modify the embodiments
 10 without departing from the scope and spirit of the present invention.